

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

**THIS PAGE BLANK (USPTO)**




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>G01H 3/08, G01M 3/24</b>		<b>A1</b>	(11) International Publication Number: <b>WO 95/25264</b>
		(43) International Publication Date: 21 September 1995 (21.09.95)	
(21) International Application Number: PCT/US95/02904 (22) International Filing Date: 10 March 1995 (10.03.95) (30) Priority Data: 08/213,129                      15 March 1994 (15.03.94)                      US (71) Applicant: ENERGY AND ENVIRONMENTAL TECHNOLOGIES CORP. [US/US]; P.O. Box 15014, Santa Rosa, CA 95402 (US). (72) Inventor: JORDAN, John; P.O. Box 1257, Oldsmar, FL 34677 (US). (74) Agents: BERKLEY, Richard, G. et al.; Brumaugh, Graves, Donohue & Raymond, 30 Rockefeller Plaza, New York, NY 10112 (US).		(81) Designated States: BR, CA, JP, KP, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).  <b>Published</b> <i>With international search report.          Before the expiration of the time limit for amending the claim and to be republished in the event of the receipt of amendments.</i>	

(54) Title: APPARATUS AND METHOD FOR DETECTING ULTRASONIC WAVES PROPAGATED FROM WITHIN A SELECTED DISTANCE

## (57) Abstract

An ultrasonic leak detector (10) which discriminates against leak signals originating from outside a desired detection zone. Incoming ultrasonic waves are divided into mutually exclusive low (30) and high (31) frequency signals which are processed to form an intensity ratio (24). The intensity ratio is compared to a pre-selected ratio (25), and the leak signals originating from outside the desired detection zone are ignored. The presence of a leak is indicated by audio (29, 34) and visual (34) devices.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

- 1 -

DescriptionApparatus and Method for Detecting Ultrasonic  
Waves Propagated from Within a Selected DistanceField of the Invention

The present invention relates in general to ultrasonic source detection systems, and in particular, to an ultrasonic source detection system that processes ultrasonic signals received from two mutually exclusive  
5 frequency spectrums, thereby enabling the system to detect signals originating from within a desired detection zone, while ignoring signals emanating from outside the desired detection zone.

10 Background of the Invention

Detection of ultrasonic signals can be useful in various situations. A common example is the detection of leaks in equipment using compressed air or other gases, such as lines and hoses used to supply  
15 compressed air to pneumatic power tools and equipment in industrial settings. Leaks can occur as a result of cuts or cracks in the lines, and ultrasonic waves are generated as compressed air escapes through a cut or crack. For reasons of safety and economy it is  
20 essential that compressed air lines be continuously monitored for defects.

A basic knowledge of sound wave principles is necessary for the understanding of the process of detecting leaks by analyzing ultrasonic waves. The  
25 audible sound wave spectrum covers wave frequencies beginning at 20 Hz and ending at 20 KHz. Waves with higher frequencies are considered ultrasonic. Sound emanating from a source will typically be a composite of waves over a wide frequency range. As a wave

- 2 -

travels farther away from its source it attenuates or flattens out, and it is well known in the art that higher frequency waves attenuate at faster rates than low frequency waves.

5 Numerous prior art devices have been developed to detect leaks. U.S. Patent No. 3,462,240 discloses an instrument which detects and amplifies acoustic vibrations caused by fluid flowing through a hole in a pipeline. It divides the vibrations into high and low  
10 frequencies, and produces an alarm when one signal band generates a higher intensity than the other signal band.

U.S. Patent No. 5,040,409 provides for an apparatus and method for detecting when a pipe break in  
15 a sprinkler system occurs. This device also generates an alarm when one band produces a higher intensity reading than the other band.

U.S. Patent No. 4,635,042 shows a device for locating the sources of ultrasonic sound within a  
20 narrow frequency band indigenous to vacuum leaks through the utilization of a hand-held probe containing a transducer exhibiting a sensitivity peak within the band at about 40 KHz, and at least one other sensitivity peak outside the narrow band.

25 U.S. Patents Nos. 4,289,019, 4,785,659, 4,858,462 and 4,958,296 also propose devices for detecting leaks in pipes or hoses.

While the foregoing devices are effective in detecting leaks and are in widespread use, they are  
30 subject to high levels of interference originating from other sources and often give false indications of a leak in response to detection of ultrasonic signals from sources other than gas leaks that are commonly present in industrial environments. Moreover, when two  
35 ultrasonic leaks exist simultaneously, previously known devices are often incapable of distinguishing between

- 3 -

leaks within the desired detection zone and leaks outside the desired detection zone.

Accordingly, it is desirable to have an ultrasonic leak detector apparatus that can distinguish between  
5 simultaneous leaks within a selected detection zone and leaks outside the zone, and eliminate additional interference to indicate only sources within the selected zone.

#### 10 Summary of the Invention

The present invention is an apparatus and method to distinguish ultrasonic waves propagating from within a desired distance while discriminating against ultrasonic sources transmitted from outside the desired  
15 detection area. The invention will produce an output signal which represents only the ultrasonic waves propagated from within the desired distance.

The preferred embodiment of the device for detecting ultrasonic waves within a desired detection  
20 zone includes low and high detectors sensitive to mutually exclusive frequencies, signal processors for producing normalized intensity and frequency signals in the respective channels, a ratio detector which continuously compares the ratio of the normalized low  
25 and high intensity signals to selected ratios thereby producing amplitude signals indicating the intensity of signals within the selected range and correcting for signals outside the range, and signal processors which process the frequency signals and the amplitude signals  
30 to produce an output signal indicative of the ultrasonic leak with background interference removed.

It is a further object of the present invention to provide a system with an adjustable ratio detector allowing the user to vary the size of the detection  
35 zone to meet a wide range of applications and detection distances.

- 4 -

It is another object of the present invention to provide a system with a numerical display whose scale is repeatable and directly proportional to the intensity of the incident ultrasound with the interference from ultrasound waves outside a selected zone removed.

It is yet a further object of the present invention to provide a system with an audible output allowing the user to hear sounds representative of the intensity and frequency variations in ultrasonic signals with the interference removed.

#### Brief Description of the Drawing

Further objects, features and advantages of the invention will become apparent from the following detailed description taken in conjunction with the accompanying figures showing a preferred embodiment of the invention, on which:

Fig. 1 is a schematic diagram of an ultrasonic wave detection apparatus in accordance with the invention;

Fig. 2 is a schematic diagram of the ratio detector portion of the apparatus; and

Fig. 3 is a flow chart illustrating a process in the ratio detector of Fig. 2.

#### Description of an Embodiment

The present invention is directed to an apparatus for ultrasonic source detection which ignores ultrasonic leaks emanating outside a desired detection zone. The invention applies the principle that high frequency waves attenuate more rapidly than low frequency waves to significantly improve ultrasonic wave detection. At an established distance, a predictable attenuation ratio can be developed by comparing the high frequency attenuation at that



- 5 -

distance to the low frequency attenuation at that distance.

Since high frequency waves attenuate more rapidly, the attenuation ratio will decrease as the ultrasonic waves travel farther from the source. Thus a compressed air leak at five feet away will have a higher ratio than a leak at twenty five feet away. The high frequency wave at five feet will have attenuated less with respect to its corresponding low frequency wave than at twenty five feet.

Figure 1 is a schematic diagram of an ultrasonic wave detection apparatus in accordance with the invention. Apparatus 10 comprises two detectors monitoring mutually exclusive frequencies. Low frequency detector 15 monitors ultrasonic waves in the low frequency spectrum (e.g., 30-40 kHz.) producing low frequency signal 30, and high frequency detector 16 monitors ultrasonic waves in the high frequency spectrum (e.g., 40-50 kHz.) producing high frequency signal 31. Detectors 15 and 16 comprise piezoelectric transducers in this preferred embodiment.

In a manner more fully described below, signal processing means 17 in the low frequency band continuously processes low frequency signal 30 to produce corresponding intensity signal 20 and amplified frequency signal 19, which correspond to the low frequency signals produced at the ultrasonic source, and signal processing means 18 in the high frequency band continuously processes high frequency signal 31 to produce corresponding intensity signal 22 and amplified frequency signal 21, which correspond to the high frequency signals produced at the ultrasonic source. Processing means 17, 18 can each comprise an operational amplifier whose input is connected to respective frequency signals 30, 31. Each operational amplifier's output is connected to a scaler (not shown)

in series to produce the corresponding normalized low frequency intensity signal 20 and high frequency intensity signal 22. Each operational amplifier's output signal is also connected to a voltage to  
5 frequency (V-to-F) converter (not shown) to produce the respective amplified frequency signals 19, 21. Intensity signals 20, 22 are connected to ratio detector 23 and amplified frequency signals 19, 21 are connected to signal processor 26. Processing means 17,  
10 18 can also include a feedback loop that automatically adjusts the amplifier gain with reference to the level of the incident ultrasonic source. The amplifier preferably has a constant high gain..

Ratio detector 23 forms intensity ratios by  
15 dividing normalized high frequency intensity 22 by low frequency intensity 20 and compares them to a selected ratio which corresponds to the expected attenuation rates of the low and high frequency signals at an established distance. The selected distance is chosen  
20 by range selector means 32 such as a switch located on an external surface of apparatus 10 that produces range signal 25 indicating the desired range of detection. Range selector means 32 can also be an attachable keyboard that communicates with ratio detector 23.  
25 Ratio detector 23 then produces an amplitude signal 24 indicative of only the leaks emanating from within the selected range and based on a comparison of the ratios described in more detail below.

When a leak exists within the desired detection  
30 zone, signal processor 26 produces a representative output 33 representative of the intensity of the detected ultrasonic wave without interference. As shown in Fig. 1, the output 33 is applied to a numerical display 34, which is of conventional design  
35 with a repeatable scale and is directly proportional to the intensity of the incident ultrasound with the

- 7 -

interference from the ultrasound waves outside a selected zone removed. Signal processor 26 also reduces the frequency to an audible range and produces a second output 27 which is a representative audible  
5 tone varied in frequency and intensity relative to the incident ultrasonic source. Audible output 27 is then connected to speaker 28 or headphones 29 of conventional design.

Figure 2 is a block diagram of ratio detector 23.  
10 Ratio detector 23 contains microprocessor 50, which performs, inter alia, data retrieval from memory 52 and comparisons between the retrieved data and a ratio of the inputs. Microprocessor 50 is connected to memory 52 and to analog to digital (A/D) converters 56 and 58  
15 which convert the incoming analog signals 20 and 22 to digital signals 60 and 62, respectively. The microprocessor 50 also receives as an input the selected range signal 25. Leads 54 connect microprocessor 50 to memory 52. Leads 60 and 62  
20 connect microprocessor 50 to low frequency A/D converter 60 and high frequency A/D converter 62, respectively. Memory 52 can comprise a programmable read only memory (PROM) chip of conventional design. As depicted in Fig. 2, the microprocessor 50 generates  
25 amplitude signal 24 as an output, which is indicative of the intensity of the detected ultrasonic waves emanating within the selected distance zone.

Figure 3 describes the process employed in ratio detector 23 shown in Figure 2. In step 102, A/D  
30 converters 60 and 62 convert the analog intensity signals to equivalent digital signals to make them compatible with the inputs of microprocessor 50. Microprocessor 50 then processes the signals and creates an intensity ratio by dividing the high  
35 frequency intensity signal 22 by the low frequency intensity signal 20 in step 104. In step 106,

microprocessor 50 retrieves the chosen ratio stored in memory 52 based on the selected range signal 25 which corresponds to the chosen range of detection. Thus if a five foot range is selected, the associated selected ratio will be different than if a 20 foot range is selected. The ratios stored in memory 52 are entered prior to the detection process and can be established through controlled testing. Therefore, the detection zones can be completely user defined based upon the ratios entered for a given application.

Microprocessor 50 then compares the intensity ratio with the selected ratio in step 108. If the intensity ratio is greater than or equals the selected ratio, the detected ultrasonic signal is known to be generated from within the selected range because of the level of attenuation, and, as indicated in step 109, ratio detector 23 generates an amplitude signal 24 whose amplitude is representative of the intensity of the detected ultrasonic waves. Therefore, the amplitude of amplitude signal 24 is directly proportional to either the high frequency intensity signal 20 or the low frequency signal 22, both of which are inputs to ratio detector 23. The amplitude signal 24 will then be displayed on selected display devices. If the intensity ratio is less than the selected ratio, the process continues. In step 110, if the intensity ratio is greater than or equal to the selected ratio less a specified percentage (10% in this preferred embodiment), this indicates some interference from another source or general noise and the intensity signal 20 or 22 is reduced by the proportional difference of the ratios to produce an amplitude signal 24 that corresponds to the selected ratio in step 112. This eliminates any noise or other signal source outside the desired range causing interference. If the intensity ratio is less than a selected ratio less a

specified percentage in step 110, then the ultrasonic wave is emanating solely from a source outside the selected range which is established from the high level of attenuation. In step 114, amplitude signal 24 is  
5 given a zero value to indicate no leaks have been identified in the desired detection zone.

The foregoing merely illustrates the principles of the invention. It will thus be appreciated that those skilled in the art will be able to devise numerous  
10 systems and methods which, although not explicitly shown or described herein, embody the principles of the invention and are thus within the spirit and scope of the invention.

For example, a person skilled in the art may use  
15 one detector in place of detectors 15 and 16. The apparatus could then include high and low frequency band pass filters of a conventional design to separate the high frequency ultrasonic waves from the low frequency ultrasonic waves. In a similar manner,  
20 signal processing means 17 and 18 could be combined into one means with additional inputs and outputs to process both high and low ultrasonic frequency signals.

Alternatively, signal processing means 17 and 18 could be incorporated digitally into the programming of  
25 ratio detector 23. This would enable the frequency signals 30 and 31 to be modified digitally using conventional digital signal processing techniques after they have passed through the A/D converters 56 and 58. This could be beneficial to minimize components  
30 failures.

Finally, the present invention has been described and disclosed in a form in which the various system functions are performed by discrete functional blocks. However, any one or more of these functions could  
35 equally well be performed by one or more appropriately programmed microprocessors, micro-coded chips, etc.

Claims

- 1     1.     An ultrasonic wave detection apparatus comprising:  
2             detection means for sensing ultrasonic waves  
3             and generating a first input signal produced from  
4             a selected lower range of frequencies from the  
5             ultrasonic waves and a second input signal  
6             produced from a selected higher range of  
7             frequencies from the ultrasonic waves;  
8             processing means for processing said first  
9             input signal to produce a first frequency signal  
10            and a first normalized intensity signal indicative  
11            of the frequency and the intensity of said first  
12            input signal, respectively, and for processing  
13            said second input signal to produce a second  
14            frequency signal and a second normalized intensity  
15            signal indicative of the frequency and the  
16            intensity of the second input signal,  
17            respectively;  
18            means for continuously comparing said first  
19            and second normalized intensity signals and  
20            producing a third signal indicative of an  
21            intensity ratio of the first and second normalized  
22            intensity signals;  
23            means for selecting a desired distance from  
24            the detection apparatus within which the  
25            ultrasonic waves propagated from within said  
26            desired distance will be displayed;  
27            means for generating a fourth signal  
28            indicative of an expected intensity ratio  
29            corresponding to ultrasonic waves propagated from  
30            a source located at said desired distance from  
31            said apparatus;  
32            means for continuously comparing said third  
33            signal to said fourth signal and producing a fifth

- 11 -

34 signal responsive to both said comparison and said  
35 first or second normalized intensity signals;  
36 means for processing said first and second  
37 frequency signals and said fifth signal to produce  
38 an output signal; and  
39 a notification means responsive to said  
40 output signal for producing an output indicative  
41 of said first or second input signals propagated  
42 within said desired distance of said apparatus  
43 without interference.

1 2. The apparatus according to claim 1 wherein said  
2 detecting means comprises a low frequency  
3 detecting means for producing said first input  
4 signal and a high frequency detecting means for  
5 producing said second input signal.

1 3. The apparatus according to claim 1 wherein said  
2 processing means comprises a low frequency  
3 processing means to process said first input  
4 signal and a high frequency processing means to  
5 process said second input signal.

1 4. The apparatus according to claim 1 wherein said  
2 notification means comprises a visual indicator.

1 5. The apparatus according to claim 1 wherein said  
2 notification means comprises an audible indicator.

1 6. The apparatus according to claim 1 wherein said  
2 generating means comprises:  
3 means for storing at least one said expected  
4 intensity ratio; and  
5 means for accessing at least one said  
6 expected intensity ratio responsive to said  
7 desired distance.

- 1     7.     The apparatus according to claim 6 wherein said  
2           storing means comprises a programmable read only  
3           memory (PROM) chip.
- 1     8.     The method of identifying ultrasonic waves  
2           originating within a specified distance comprising  
3           the steps of:  
4               generating a first ratio from the intensity  
5               of the high frequency ultrasonic waves to the low  
6               frequency ultrasonic waves;  
7               generating a second ratio indicative of the  
8               expected intensity ratio at said selected  
9               distance; and  
10              comparing continuously said first and second  
11              ratios and producing output signal responsive to  
12              said comparison and indicative of said ultrasonic  
13              waves within said specified distance.
- 1     9.     An ultrasonic wave detection method comprising the  
2           steps of:  
3               sensing ultrasonic waves and generating a  
4               first input signal produced from a selected lower  
5               range of frequencies from the ultrasonic waves and  
6               a second input signal produced from a selected  
7               higher range of frequencies from the ultrasonic  
8               waves;  
9               processing said first input signal to produce  
10              a first frequency signal and a first normalized  
11              intensity signal indicative of the frequency and  
12              the intensity of said first input signal,  
13              respectively, and processing said second input  
14              signal to produce a second frequency signal and a  
15              second normalized intensity signal indicative of  
16              the frequency and the intensity of the second  
17              input signal, respectively;



- 13 -

18           comparing continuously said first and second  
19           normalized intensity signals and producing a third  
20           signal indicative of an intensity ratio of the  
21           first and second normalized intensity signals;  
22           selecting a desired distance from the  
23           detection apparatus within which the ultrasonic  
24           waves propagated from within said desired distance  
25           will be displayed;  
26           generating a fourth signal indicative of an  
27           expected intensity ratio corresponding to  
28           ultrasonic waves propagated from a source located  
29           at said desired distance from said apparatus;  
30           comparing continuously said third signal to  
31           said fourth signal and producing a fifth signal  
32           responsive to both said comparison and said first  
33           or second intensity signals;  
34           processing said first and second frequency  
35           signals and said fifth signal to produce an output  
36           signal; and  
37           producing an output responsive to said output  
38           signal indicative of said first or second input  
39           signals propagated within said desired distance of  
40           said apparatus without interference.




FIG. 1




FIG. 2




FIG. 3

# INTERNATIONAL SEARCH REPORT

In national Application No.  
PCT/US 95/02904

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 6 G01H3/08 G01M3/24

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 6 G01H G01M G01V

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	DE-A-31 01 928 (MESSERSCHMITT BOELKOW BLOHM) 5 August 1982 see the whole document ---	1,8
Y	US-A-3 903 729 (COVINGTON MORRIS T) 9 September 1975 see abstract; claims 1,3,5 ---	1,8
A	US-A-4 287 581 (NEALE SR DORY J) 1 September 1981 see abstract; figure 3 ---	4,5
A	FR-A-1 530 919 (SHELL INTERNATIONALE RESEARCH MAATSCHAPPIJ N.V.) 24 October 1968 ---	
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents :

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*I\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*&\* document member of the same patent family

Date of the actual completion of the international search

30 June 1995

Date of mailing of the international search report

26.07.95

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax (+31-70) 340-3016

Authorized officer

de Heering, P

# INTERNATIONAL SEARCH REPORT

In. .tional Application No  
PCT/US 95/02904

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US-A-4 201 092 (DAU GARY J) 6 May 1980 see column 1, line 29-- column 2, line 5; claim; figure 2 ---	1
A	PATENT ABSTRACTS OF JAPAN vol. 011 no. 129 (P-570) ,23 April 1987 & JP,A,61 271476 (NEC CORP) 1 December 1986, see abstract ---	1,8
A	PATENT ABSTRACTS OF JAPAN vol. 013 no. 329 (P-904) ,25 July 1989 & JP,A,01 094205 (HITACHI CONSTR MACH CO LTD) 12 April 1989, see abstract -----	1,8

# INTERNATIONAL SEARCH REPORT

International Application No.

PCT/US 95/02904

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE-A-3101928	05-08-82	NONE	
US-A-3903729	09-09-75	CA-A- 1010554	17-05-77
		DE-A- 2414453	24-10-74
		GB-A- 1438237	03-06-76
		JP-A- 50002990	13-01-75
		CA-A- 963143	18-02-75
		DE-A- 2162708	27-07-72
		DE-B- 2167142	19-06-80
		GB-A- 1374797	20-11-74
US-A-4287581	01-09-81	NONE	
FR-A-1530919	24-10-68	AT-A- 290167	15-03-71
		CH-A- 486017	15-02-70
		DE-A- 1650173	10-09-70
		GB-A- 1149284	
		NL-A- 6609733	15-01-68
		US-A- 3462240	19-08-69
US-A-4201092	06-05-80	NONE	


**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup> :</b> <b>G01H 3/08, G01M 3/24</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 95/25264</b> <b>(43) International Publication Date:</b> 21 September 1995 (21.09.95)
<b>(21) International Application Number:</b> PCT/US95/02904 <b>(22) International Filing Date:</b> 10 March 1995 (10.03.95) <b>(30) Priority Data:</b> 08/213,129 15 March 1994 (15.03.94) US <b>(71) Applicant:</b> ENERGY AND ENVIRONMENTAL TECHNOLOGIES CORP. [US/US]; P.O. Box 15014, Santa Rosa, CA 95402 (US). <b>(72) Inventor:</b> JORDAN, John; P.O. Box 1257, Oldsmar, FL 34677 (US). <b>(74) Agents:</b> BERKLEY, Richard, G. et al.; Brumaugh, Graves, Donohue & Raymond, 30 Rockefeller Plaza, New York, NY 10112 (US).		<b>(81) Designated States:</b> BR, CA, JP, KP, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).  <b>Published</b> <i>With international search report.</i> <i>With amended claims.</i>  <b>Date of publication of the amended claims:</b> 26 October 1995 (26.10.95)

**(54) Title:** APPARATUS AND METHOD FOR DETECTING ULTRASONIC WAVES PROPAGATED FROM WITHIN A SELECTED DISTANCE**(57) Abstract**

An ultrasonic leak detector (10) which discriminates against leak signals originating from outside a desired detection zone. Incoming ultrasonic waves are divided into mutually exclusive low (30) and high (31) frequency signals which are processed to form an intensity ratio (24). The intensity ratio is compared to a pre-selected ratio (25), and the leak signals originating from outside the desired detection zone are ignored. The presence of a leak is indicated by audio (29, 34) and visual (34) devices.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				



## AMENDED CLAIMS

[received by the International Bureau on 26 September 1995 (26.09.95);  
original claims 1-9 replaced by amended claims 1-18 (8 pages)]

- 1     1.     An ultrasonic wave detection apparatus,  
2           comprising:  
3               means for detecting ultrasonic waves and  
4               generating a first input signal responsive to said  
5               ultrasonic waves of a selected low frequency and  
6               for generating a second input signal responsive to  
7               said ultrasonic waves of a selected high  
8               frequency, wherein said selected low and high  
9               frequencies are mutually exclusive;  
10               means for processing said first input signal  
11               to produce a first frequency signal and a first  
12               intensity signal indicative of the frequency and  
13               the intensity, respectively, of said first input  
14               signal and for processing said second input signal  
15               to produce a second frequency signal and a second  
16               intensity signal indicative of the frequency and  
17               the intensity, respectively, of the second input  
18               signal;  
19               means for continuously comparing said first  
20               and second intensity signals and producing a third  
21               signal indicative of an intensity ratio of the  
22               first and second intensity signals;  
23               means for selecting a distance from the  
24               detection apparatus wherein only ultrasonic waves  
25               propagated from a source located within said  
26               desired distance will be indicated by said  
27               apparatus;  
28               means for generating a fourth signal  
29               indicative of an expected intensity ratio  
30               corresponding to low frequency and high frequency  
31               ultrasonic waves propagated from a source located  
32               at said selected distance from said apparatus;  
33               means for continuously comparing said third  
34               signal and said fourth signal, and when a

35 predetermined relationship exists between said  
36 intensity ratio of said first and second intensity  
37 signals and said expected ratio signal, producing  
38 a fifth signal representative of the intensity of  
39 at least one of said first and second intensity  
40 signals;

41 means for processing at least one of said  
42 first and second frequency signals and said fifth  
43 signal to produce an output signal; and

44 notification means responsive to said output  
45 signal for producing an output indicative of at  
46 least one of said first and second input signals  
47 propagated from a source located within said  
48 selected distance of said apparatus without  
49 interference.

1 2. The apparatus according to claim 1, wherein said  
2 detection means comprises a low frequency  
3 detecting means for producing said first input  
4 signal and a high frequency detection means for  
5 producing said second input signal.

1 3. The apparatus according to claim 1, wherein said  
2 processing means comprises a low frequency  
3 processing means to process said first input  
4 signal and a high frequency processing means to  
5 process said second input signal.

1 4. The apparatus according to claim 1, wherein said  
2 notification means comprises at least one of a  
3 visual indicator and an audible indicator.

1 5. The apparatus according to claim 1, wherein said  
2 fourth signal generating means comprises:  
3 means for storing at least one said expected  
4 intensity ratio; and

5 means for accessing said at least one  
6 expected intensity ratio in response to the  
7 selection of said selected distance by said  
8 selecting means.

1 6. The apparatus according to claim 5, wherein said  
2 storing means comprises a programmable read only  
3 memory (PROM) chip.

1 7. The apparatus of claim 1, wherein said fifth  
2 signal is representative of an average of said  
3 first and second intensity signals.

1 8. The apparatus of claim 1, wherein said  
2 notification means produces an output indicative  
3 of an average of said first and second frequency  
4 signals and an average of said first and second  
5 intensity signals.

1 9. The apparatus of claim 1, wherein when said  
2 intensity ratio of said first and second intensity  
3 signals is greater than or equal to said expected  
4 intensity ratio, said fifth signal is directly  
5 related to at least one of said first and second  
6 intensity signals.

1 10. The apparatus of claim 10, wherein when said  
2 intensity ratio of said first and second intensity  
3 signals is less than the expected intensity ratio  
4 and greater than or equal to said expected  
5 intensity ratio less a selected percentage, said  
6 fifth signal's amplitude is proportionally greater  
7 than at least one of said first and second  
8 intensity signals.

1 11. The apparatus in claim 11, wherein when said  
2 intensity ratio of said first and second intensity  
3 signals is less than the expected intensity ratio  
4 less a selected percentage, said fifth signal's  
5 amplitude is zero and no output signal is  
6 produced.

1 12. An ultrasonic wave detection method comprising the  
2 steps of:

3 detecting ultrasonic waves and generating a  
4 first input signal produced responsive to said  
5 ultrasonic waves of a selected low frequency and  
6 generating a second input signal produced  
7 responsive to said ultrasonic waves of a selected  
8 higher frequency, wherein said selected low and  
9 high frequencies are mutually exclusive;

10 processing said first input signal to produce  
11 a first frequency signal and a first intensity  
12 signal indicative of the frequency and the  
13 intensity, respectively, of said first input  
14 signal and processing said second signal to  
15 produce a second input frequency signal and a  
16 second intensity signal indicative of the  
17 frequency and the intensity, respectively, of the  
18 second input signal;

19 continuously comparing said first and second  
20 intensity signals and producing a third signal  
21 indicative of an intensity ratio of the first and  
22 second intensity signals;

23 selecting a distance from a detection  
24 apparatus which detects said ultrasonic waves  
25 wherein only ultrasonic waves propagated from a  
26 source located within said selected distance from  
27 said apparatus will be indicated;

28 generating a fourth signal indicative of an  
29 expected intensity ratio corresponding to low

30 frequency and high frequency ultrasonic waves  
31 propagated from a source located at said selected  
32 distance from the point of detection of the  
33 ultrasonic waves;

34 continuously comparing said third signal to  
35 said fourth signal and, when a predetermined  
36 relationship exists between said intensity ratio  
37 of said first and second intensity signals and  
38 said expected intensity ratio, producing a fifth  
39 signal representative of at least one of said  
40 first and second intensity signals;

41 processing said first and second frequency  
42 signals and said fifth signal to produce an output  
43 signal; and

44 producing an output responsive to said output  
45 signal indicative of at least one of said first  
46 and second input signals propagated from a source  
47 located within said selected distance.

1 13. The method of claim 13, wherein when said  
2 intensity ratio of said first and second intensity  
3 signals is greater than or equal to the expected  
4 intensity ratio, said fifth signal is directly  
5 related to at least one of said first and second  
6 intensity signal.

1 14. The method of claim 14, wherein when said  
2 intensity ratio of said first and second intensity  
3 signals is less than the expected intensity ratio  
4 and greater than or equal to said expected  
5 intensity ratio less a selected percentage, said  
6 fifth signal's amplitude is proportionally greater  
7 than at least one of said first and second  
8 intensity signals.

- 1 15. The method in claim 15, wherein when said  
2 intensity ratio of said first and second intensity  
3 signals is less than the expected intensity ratio  
4 less a selected percentage, said fifth signal's  
5 amplitude is zero and no output signal is  
6 produced.
- 1 16. The method of claim 13, wherein said fifth signal  
2 is representative of an average of said first and  
3 second intensity signals.
- 1 17. An ultrasonic wave detection apparatus comprising:  
2 means for detecting ultrasonic waves and  
3 generating a first input signal responsive to said  
4 ultrasonic waves of a selected low frequency and  
5 for generating a second input signal responsive to  
6 said ultrasonic waves of a selected high  
7 frequency, wherein said selected low and high  
8 frequencies are mutually exclusive;  
9 means for processing said first input signal  
10 to produce a first intensity signal indicative of  
11 the intensity of said first input signal and for  
12 processing said second input signal to produce a  
13 second intensity signal indicative of the  
14 intensity of the second input signal;  
15 means for continuously comparing said first  
16 and second intensity signals and producing a third  
17 signal indicative of an intensity ratio of the  
18 first and second intensity signals;  
19 means for selecting a distance from the  
20 detection apparatus within which sources of  
21 ultrasonic waves are to be indicated to the  
22 exclusion of sources beyond said distance;  
23 means for generating a fourth signal  
24 indicative of an expected intensity ratio  
25 corresponding to low frequency and high frequency

- 26 ultrasonic waves propagated from a source located  
27 at said selected distance from said apparatus;  
28 means for continuously comparing said third  
29 signal and said fourth signal, and when a  
30 predetermined relationship exists between said  
31 intensity ratio of said first and second intensity  
32 signals and said expected intensity ratio exists,  
33 producing a fifth signal indicative of at least  
34 one of said first and second intensity signals;  
35 and  
36 notification means responsive to said fifth  
37 signal for producing an output indicative of at  
38 least one of said first and second intensity  
39 signals propagated from a source located within  
40 said selected distance of said apparatus without  
41 interference.
- 1 18. A method of identifying ultrasonic waves  
2 originating within a predetermined distance,  
3 comprising the steps of:  
4 sensing ultrasonic waves having a high  
5 frequency component and a low frequency component;  
6 separately determining an intensity of the  
7 high frequency component and an intensity of the  
8 low frequency component;  
9 generating a first ratio of the intensity of  
10 the high frequency ultrasonic waves to the  
11 intensity of the low frequency ultrasonic waves;  
12 generating a second ratio indicative of the  
13 expected intensity ratio at said predetermined  
14 distance; and  
15 comparing continuously said first and second  
16 ratios and producing an output signal indicative  
17 of the detection of ultrasonic waves within said  
18 predetermined distance when a predetermined

19           relationship between said first and second ratios  
20           exists.